



<u>Product Information</u>	
<b>SKU:</b>	12V-MB-WW-12M 12V-MB-PW-12M 12V-MB-CW-12M
<u>Photometrics</u>	
<b>Kelvin Temperature / Color Rendering Index (CRI)</b>	Warm 3000K / 92 CRI Pure 4200K / 93 CRI Cool 6000K / 92 CRI
<u>Dimensions</u>	
<b>Width</b>	8mm
<b>Length</b>	12M (39.37')

<u>Qualifications</u>	
<b>Certification</b>	CSA 265216
<b>Compliance</b>	Class 2
<b>IP Rating</b>	IP65
<b>Lamp Life</b>	50,000 Hours
<b>Warranty</b>	2 Year
<u>Specifications</u>	
<b>Voltage</b>	12V DC
<b>Lumens / Watt</b>	See chart below
<b>Watts / Foot</b>	3W / Ft.
<b>Diode Size</b>	2835
<b>Diode Spacing</b>	120LED/M, 0.33"
<b>Cut Points</b>	1.0" (Every 3 LEDs)
<b>Installation</b>	3M Adhesive Liner
<b>Dimmable</b>	Yes

Specifications:	Voltage	LED Density	Wattage	Luminosity	Color Temp	CRI
Warm White	12V	36 LEDs/ft., 120 LEDs/m	3W/ft.	260 lm/ft.	3000K	92
Pure White	12V	36 LEDs/ft., 120 LEDs/m	3W/ft.	275 lm/ft.	4200K	93
Cool White	12V	36 LEDs/ft., 120 LEDs/m	3W/ft.	280 lm/ft.	6000K	92

