



<b>Product Information</b>	
<b>SKU:</b>	UB-3200-OUTDOOR-C UB-4200-OUTDOOR-C UB-6500-OUTDOOR-C
<b>Photometrics</b>	
<b>Kelvin Temperature / Color Rendering Index (CRI)</b>	<b>Warm</b> 3000K / 92 CRI <b>Pure</b> 4200K / 93 CRI <b>Cool</b> 6000K / 92 CRI
<b>Dimensions</b>	
<b>Width</b>	(W) 0.5" , (H) 0.16"
<b>Length</b>	Custom Length, ~20' Max

<b>Qualifications</b>	
<b>Certification</b>	CSA 265216
<b>Compliance</b>	Class 2
<b>IP Rating</b>	IP67
<b>Lamp Life</b>	50,000 Hours
<b>Warranty</b>	2 Year
<b>Specifications</b>	
<b>Voltage</b>	12V DC
<b>Lumens / Watt</b>	See chart below
<b>Watts / Foot</b>	2.75W / Ft.
<b>Diode Size</b>	2835
<b>Diode Spacing</b>	99LED/M, 0.39"
<b>Cut Points</b>	1.06" (Every 3 LEDs)
<b>Cable Lead Length</b>	3 Ft., 18/2 AWG
<b>Dimmable</b>	Yes

Specifications:	Voltage	LED Density	Wattage	Luminosity	Color Temp	CRI
Warm White	12V	30 LEDs/ft., 99 LEDs/m	2.75 W/ft.	220 lm/ft.	3000K	92
Pure White	12V	30 LEDs/ft., 99 LEDs/m	2.75 W/ft.	235 lm/ft.	4200K	93
Cool White	12V	30 LEDs/ft., 99 LEDs/m	2.75 W/ft.	240 lm/ft.	6000K	92

